



FUJIAN SURIRELLA ELECTRICAL MACHINERY CO.,LTD

www.pluspowergenerator.com sales1@plus-power.cn Mobile/wechat/whatsapp:+86-13959393353



50Hz/1500rpm PLUS POWER CUMMINS Diesel Generator Set (Page 1/3)

Genset Model	PC25	PC30	PC30	PC33	PC45	PC45	PC66	PC70	
Standby Power	25kVA	30kVA	30kVA	33kVA	45kVA	45kVA	66kVA	70kVA	
	20kW	24kW	24kW	26kW	36kW	36kW	53kW	56kW	
Prime Power	22kVA	28kVA	28kVA	30kVA	40kVA	40kVA	60kVA	65kVA	
	18kW	22kW	22kW	24kW	32kW	32kW	48kW	52kW	
Ampere (base on 400V) A	32.5	39.7	39.7	43.3	57.7	57.7	86.6	93.8	
Engine Brand	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	
Engine Model	4B3.9-G1	4B3.9-G1	4B3.9-G2	4B3.9-G12	4BT3.9-G1	4BT3.9-G2	4BTA3.9-G2	4BTA3.9-G2	
Cylinder *Bore*Stroke	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	
Displacement	3.92L	3.92L	3.92L	3.92L	3.92L	3.92L	3.92L	3.92L	
Alternator Brand	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	
Alternator Model	184E	184F	184F	184G	184J	184J	224E	224F	
Alternator type	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	
Controller Model	6120	6120	6120	6120	6120	6120	6120	6120	
Fuel consumption	5.8L/h	6.9L/h	6.9L/h	7.8L/h	9.7L/h	9.7L/h	12.5L/h	14.5L/h	
Capacity(L)	Fuel tank	60L	70L	70L	80L	100L	100L	120L	145L
	Coolant	19L	19L	19L	19L	19L	19L	19L	19L
	Lubrication	10.9L	10.9L	10.9L	10.9L	10.9L	10.9L	10.9L	10.9L
Open type	Demension	1550*740*1270	1650*740*1270	1650*740*1270	1650*740*1270	1700*740*1270	1700*740*1270	1800*780*1330	1800*780*1330
	Weight	720KGS	760KGS	760KGS	770KGS	840KGS	840KGS	880KGS	900KGS
Sound proof	Dimension	2100*950*1300	2100*950*1300	2100*950*1300	2200*950*1300	2200*950*1300	2200*950*1300	2300*1000*1300	2400*1000*1300
	Weight	1030KGS	1060KGS	1060KGS	1100KGS	1150KGS	1150KGS	1200KGS	1240KGS

50Hz/1500rpm PLUS POWER CUMMINS Diesel Generator Set (Page 2/3)

Genset Model	PC88	PC110	PC110	PC115	PR125	PC145	PC170	PC200	
Standby Power	88kVA	110kVA	110kVA	115kVA	125kVA	145kVA	170kVA	200kVA	
	70kW	88kW	88kW	92kW	100kW	116kW	136kW	160kW	
Prime Power	80kVA	100kVA	100kVA	105kVA	115kVA	135kVA	155kVA	180kVA	
	64kW	80kW	80kW	84kW	92kW	108kW	124kW	144kW	
Ampere (base on 400V) A	115.5	144.3	144.3	151.6	166.0	194.9	223.7	259.8	
Engine Brand	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	
Engine Model	4BTAA3.9-G11	6BT5.9-G1	6BT5.9-G2	6BTA5.9-G2	6BTA5.9-G2	6BTAA5.9-G2	6BTAA5.9-G12	6CTA8.3-G1	
Cylinder *Bore*Stroke	4×102×120mm	6×102×120mm	6×102×120mm	6×102×120mm	6×102×120mm	6×102×120mm	6×102×120mm	6×114×135mm	
Displacement	3.92L	5.9L	5.9L	5.9L	5.9L	5.9L	5.9L	8.3L	
Alternator Brand	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	
Alternator Model	224G	274C	274C	274D	274D	274E	274F	274G	
Alternator type	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	
Controller Model	6120	6120	6120	6120	6120	6120	6120	6120	
Fuel consumption	17.1L/h	21L/h	21L/h	23.8L/h	26.3L/h	29.4L/h	33.4L/h	41.2L/h	
Capacity(L)	Fuel tank	170L	210L	210L	240L	260L	300L	330L	400L
	Coolant	19L	22.4L	22.4L	22.4L	22.4L	22.4L	22.4L	30.6L
	Lubrication	10.9L	16.4L	16.4L	16.4L	16.4L	16.4L	16.4L	27.6L
Open type	Demension	1850*780*1330	2150*900*1400	2150*900*1400	2150*900*1400	2150*900*1400	2350*900*1400	2350*900*1400	2350*900*1400
	Weight	1000KGS	1170KGS	1170KGS	1200KGS	1200KGS	1270KGS	1310KGS	1670KGS
Sound proof	Dimension	2500*1000*1300	2800*1100*1500	2800*1100*1500	2800*1100*1500	2800*1100*1500	3000*1100*1500	3000*1100*1500	3200*1100*1500
	Weight	1340KGS	1600KGS	1600KGS	1630KGS	1630KGS	1760KGS	1800KGS	2170KGS
Genset Model	PC200	PC220	PC275	PC275	PC315	PC360	PC385	PC440	
Standby Power	200kVA	220kVA	275kVA	275kVA	315kVA	360kVA	385kVA	440kVA	
	160kW	176kW	220kW	220kW	252kW	288kW	308kW	352kW	
Prime Power	180kVA	200kVA	250kVA	250kVA	288kVA	325kVA	350kVA	400kVA	
	144kW	160kW	200kW	200kW	230kW	260kW	280kW	320kW	
Ampere (base on 400V) A	259.8	288.7	360.9	360.9	415.0	469.1	505.2	577.4	
Engine Brand	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	
Engine Model	6CTA8.3-G2	6CTAA8.3-G2	6LTAA8.9-G2	6LTAA8.9-G3	6LTAA9.5-G3	6LTAA9.5-G1	NTA855-G2A	NTAA855-G7A	
Cylinder *Bore*Stroke	6×114×135mm	6×114×135mm	6×114×145mm	6×114×145mm	6×114×148mm	6×114×148mm	6×140×152mm	6×140×152mm	
Displacement	8.3L	8.3L	8.9L	8.9L	9.5L	9.5L	14L	14L	
Alternator Brand	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	
Alternator Model	274G	274H	274K	274K	314D	314E	314E	314F	
Alternator type	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	
Controller Model	6120	6120	6120	6120	6120	6120	6120	6120	
Fuel consumption	41.2L/h	44.1L/h	50.5L/h	52.8L/h	56.8L/h	68L/h	71L/h	88L/h	
Capacity(L)	Fuel tank	400L	440L	480L	480L	520L	560L	700L	900L
	Coolant	30.6L	30.6L	34L	34L	57L	57L	20.8L	20.8L
	Lubrication	27.6L	27.6L	27.6L	27.6L	28L	28L	38.6L	38.6L
Open type	Demension	2350*900*1400	2450*900*1400	2550*1000*1750	2550*1000*1750	2650*1000*1750	2650*1000*1750	3050*1100*1900	3250*1100*1900
	Weight	1670KGS	1750KGS	1980KGS	1980KGS	2320KGS	2420KGS	2950KGS	3100KGS
Sound proof	Dimension	3200*1100*1500	3200*1200*1700	3500*1250*2000	3500*1250*2000	3800*1500*2100	3800*1500*2100	3800*1500*2100	4100*1500*2250
	Weight	2170KGS	2270KGS	2840KGS	2840KGS	3220KGS	3320KGS	3790KGS	4070KGS

50Hz/1500rpm PLUS POWER CUMMINS Diesel Generator Set (Page 3/3)

Genset Model		PC500	PC550	PC600	PC660	PC700	PC725	PC800	PC825
Standby Power		500kVA	550kVA	600kVA	660kVA	700kVA	725kVA	800kVA	825kVA
		400kW	440kW	480kW	528kW	560kW	580kW	640kW	660kW
Prime Power		450kVA	500kVA	550kVA	600kVA	625kVA	650kVA	725kVA	750kVA
		360kW	400kW	440kW	480kW	500kW	520kW	580kW	600kW
Ampere (base on 400V) A		649.5	721.7	793.9	866.1	902.1	938.2	1046.5	1082.6
Engine Brand		CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS
Engine Model		QSZ13-G2	QSZ13-G3	KTAA19-G5	KTA19-G8	KTAA19-G6A	QSKT19-G3	KTA38-GA	KTA38-G2
Cylinder *Bore*Stroke		6×130×163mm	6×130×163mm	6×159×159mm	6×159×159mm	6×159×159mm	6×159×159mm	12×159×159mm	12×159×159mm
Displacement		13L	13L	18.9L	18.9L	18.9L	18.9L	37.8L	37.8L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		354C	354D	354E	354E	354FS	354F	404B	404B
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		6120	6120	6120	6120	6120	6120	6120	6120
Fuel consumption		89.9L/h	102.2L/h	112.2L/h	126L/h	133L/h	139L/h	162L/h	166L/h
Capacity(L)	Fuel tank	720L	800L	900L	1000L	1100L	1100L	1300L	1300L
	Coolant	73L	73L	30L	30L	30L	42L	118L	118L
	Lubrication	45.4L	45.4L	38L	38L	38L	72L	114L	114L
Open type	Demension	3100*1400*2080	3100*1400*2080	3750*1450*2280	3750*1450*2280	3750*1450*2280	3900*1500*2280	4300*1800*2500	4300*1800*2500
	Weight	3200KGS	3300KGS	4000KGS	4120KGS	4180KGS	4450KGS	6950KGS	7090KGS
Sound proof	Dimension	4300*1800*2250	4300*1800*2250	4900*2000*2250	4900*2000*2250	4900*2000*2250	5100*2000*2250	5400*2200*2550	5400*2200*2550
	Weight	4450KGS	4550KGS	5320KGS	5430KGS	5490KGS	5720KGS	8150KGS	8290KGS
Genset Model		PC880	PC1000	PC1100	PC1250	PC1400	PC1500	PC1600	PC1900
Standby Power		880kVA	1000kVA	1100kVA	1250kVA	1375kVA	1515kVA	1625kVA	1875kVA
		704kW	800kW	880kW	1000kW	1100kW	1212kW	1300kW	1500kW
Prime Power		800kVA	913kVA	1000kVA	1125kVA	1250kVA	1375kVA	1475kVA	1688kVA
		640kW	730kW	800kW	900kW	1000kW	1100kW	1180kW	1350kW
Ampere (base on 400V) A		1154.7	1317.1	1443.4	1623.8	1804.3	1984.7	2129.0	2435.8
Engine Brand		CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS
Engine Model		KTA38-G2B	KTA38-G2A	KTA38-G5	KTA38-G9	KTA50-G3	KTA50-G8	KTA50-GS8	KTA50-G15
Cylinder *Bore*Stroke		12×159×159mm	12×159×159mm	12×159×159mm	12×159×159mm	16×159×159mm	16×159×159mm	16×159×159mm	16×159×159mm
Displacement		37.8L	37.8L	37.8L	37.8L	50.3L	50.3L	50.3L	50.3L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		404C	404D	404E	404F	404G	454B	454C	454D
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		6120	6120	6120	6120	6120	6120	6120	6120
Fuel consumption		178L/h	204L/h	221L/h	248L/h	273L/h	303L/h	309L/h	357L/h
Capacity(L)	Fuel tank	1400L	1400L	1400L	1400L	N/A	N/A	N/A	N/A
	Coolant	118L	118L	118L	118L	161L	165L	165L	165L
	Lubrication	114L	114L	114L	114L	151L	178L	178L	178L
Open type	Demension	4300*1800*2500	4300*1800*2500	4300*1800*2500	4600*1850*2500	5000*2150*2550	5000*2150*2550	5200*2150*2550	5300*2200*2550
	Weight	7300KGS	7360KGS	7400KGS	7700KGS	9240KGS	9860KGS	10150KGS	10590KGS
Sound proof	Dimension	5400*2200*2550	5400*2200*2550	5400*2200*2550	5800*2200*2550	6400*2200*2550	6400*2200*2550	7200*2200*2550	7600*2200*2550
	Weight	8500KGS	8560KGS	8600KGS	9100KGS	10940KGS	11560KGS	11950KGS	12690KGS

60Hz/1800rpm PLUS POWER CUMMINS Diesel Generator Set (Page 1/2)

Genset Model		PC28	PC33	PC40	PC50	PC70	PC95	PC115	PC140
Standby Power		28kVA	33kVA	40kVA	50kVA	70kVA	95kVA	115kVA	140kVA
		22kW	26kW	32kW	40kW	56kW	76kW	92kW	112kW
Prime Power		25kVA	30kVA	35kVA	45kVA	65kVA	85kVA	105kVA	125kVA
		20kW	24kW	28kW	36kW	52kW	68kW	84kW	100kW
Ampere (base on 440V) A		32.8	39.4	45.9	59.0	85.3	111.5	137.8	164.0
Engine Brand		CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS
Engine Model		4B3.9-G11	4B3.9-G2	4B3.9-G12	4BT3.9-G2	4BTA3.9-G2	4BTAA3.9-G11	6BT5.9-G2	6BT5.9-G2
Cylinder *Bore*Stroke		4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	4×102×120mm	6×102×120mm	6×102×120mm
Displacement		3.92L	3.92L	3.92L	3.92L	3.92L	3.92L	5.9L	5.9L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		184E	184E	184F	184H	224D	224F	274C	274D
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		6120	6120	6120	6120	6120	6120	6120	6120
Fuel consumption		6.4L/h	8.4L/h	9.2L/h	10.4L/h	15.1L/h	19.5L/h	27.6L/h	31.8L/h
Capacity(L)	Fuel tank	60L	70L	80L	100L	145L	170L	240L	260L
	Coolant	19L	19L	19L	19L	19L	19L	22.4L	22.4L
	Lubrication	10.9L	10.9L	10.9L	10.9L	10.9L	10.9L	16.4L	16.4L
Open type	Demension	1550*740*1270	1650*740*1270	1650*740*1270	1700*740*1270	1800*780*1330	1850*780*1330	2150*900*1400	2150*900*1400
	Weight	720KGS	730KGS	770KGS	840KGS	900KGS	1000KGS	1200KGS	1200KGS
Sound proof	Dimension	2100*950*1300	2100*950*1300	2200*950*1300	2200*950*1300	2400*1000*1300	2500*1000*1300	2800*1100*1500	2800*1100*1500
	Weight	1060KGS	1070KGS	1100KGS	1150KGS	1240KGS	1340KGS	1630KGS	1630KGS
Genset Model		PC155	PC185	PC210	PC230	PC285	PC310	PC315	PC350
Standby Power		156kVA	185kVA	210kVA	230kVA	285kVA	310kVA	315kVA	350kVA
		125kW	148kW	168kW	184kW	228kW	248kW	252kW	280kW
Prime Power		145kVA	170kVA	190kVA	210kVA	260kVA	280kVA	285kVA	320kVA
		116kW	136kW	152kW	168kW	208kW	224kW	228kW	256kW
Ampere (base on 400V) A		190.3	223.1	249.3	275.6	341.2	367.4	374.0	419.9
Engine Brand		CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS
Engine Model		6BTAA5.9-G2	6BTAA5.9-G12	6CTA8.3-G2	6CTAA8.3-G2	6LTAA8.9-G2	6LTAA8.9-G3	6LTAA9.5-G3	6LTAA9.5-G1
Cylinder *Bore*Stroke		6×102×120mm	6×102×120mm	6×114×135mm	6×114×135mm	6×114×145mm	6×114×145mm	6×114×148mm	6×114×148mm
Displacement		5.9L	5.9L	8.3L	8.3L	8.9L	8.9L	9.5L	9.5L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		274E	274E	274F	274H	274J	274J	274J	314D
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		6120	6120	6120	6120	6120	6120	6120	6120
Fuel consumption		32.9L/h	36.7L/h	42.6L/h	47.8L/h	57.5L/h	60.3L/h	59.4L/h	68L/h
Capacity(L)	Fuel tank	300L	330L	400L	440L	480L	480L	520L	560L
	Coolant	22.4L	22.4L	30.6L	30.6L	34L	34L	57L	57L
	Lubrication	16.4L	16.4L	27.6L	27.6L	27.6L	27.6L	28L	28L
Open type	Demension	2350*900*1400	2350*900*1400	2350*900*1400	2450*900*1400	2550*1000*1750	2550*1000*1750	2650*1000*1750	2650*1000*1750
	Weight	1270KGS	1310KGS	1670KGS	1750KGS	1980KGS	1980KGS	2320KGS	2420KGS
Sound proof	Dimension	3000*1100*1500	3000*1100*1500	3200*1100*1500	3200*1200*1700	3500*1250*2000	3500*1250*2000	3800*1500*2100	3800*1500*2100
	Weight	1760KGS	1800KGS	2170KGS	2270KGS	2840KGS	2840KGS	3220KGS	3320KGS

60Hz/1800rpm PLUS POWER CUMMINS Diesel Generator Set Page (2/2)

Genset Model		PC385	PC440	PC500	PC550	PC625	PC690	PC750	PC850
Standby Power		385kVA	440kVA	500kVA	550kVA	625kVA	688kVA	750kVA	850kVA
		308kW	352kW	400kW	440kW	500kW	550kW	600kW	680kW
Prime Power		350kVA	400kVA	450kVA	500kVA	563kVA	600kVA	688kVA	775kVA
		280kW	320kW	360kW	400kW	450kW	480kW	550kW	620kW
Ampere (base on 400V) A		459.3	524.9	590.5	656.1	738.1	787.3	902.1	1017.0
Engine Brand		CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS
Engine Model		NTA855-G1B	NTA855-G3	QSZ13-G2	QSZ13-G3	KTAA19-G3A	KTA19-G5	KTAA19-G6A	KTA38-G
Cylinder *Bore*Stroke		6×140×152mm	6×140×152mm	6×130×163mm	6×130×163mm	6×159×159mm	6×159×159mm	6×159×159mm	12×159×159mm
Displacement		14L	14L	13L	13L	18.9L	18.9L	18.9L	37.8L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		314D	314F	314F	314F	354C	354D	354E	354F
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		6120	6120	6120	6120	6120	6120	6120	6120
Fuel consumption		76.9L/h	87.2L/h	91.3L/h	105.4L/h	121L/h	134L/h	145L/h	154L/h
Capacity(L)	Fuel tank	700L	900L	720L	800L	900L	1000L	1100L	1300L
	Coolant	20.8L	20.8L	73L	73L	30L	30L	30L	118L
	Lubrication	38.6L	38.6L	45.4L	45.4L	38L	38L	38L	114L
Open type	Demension	3050*1100*1900	3150*1100*1900	3100*1400*2080	3100*1400*2080	3400*1350*2000	3750*1450*2280	3750*1450*2280	4300*1800*2500
	Weight	2950KGS	3100KGS	3200KGS	3300KGS	3900KGS	4000KGS	4100KGS	6650KGS
Sound proof	Dimension	3800*1500*2100	3900*1500*2100	4300*1800*2250	4300*1800*2250	4700*1800*2250	4900*2000*2250	4900*2000*2250	5400*2200*2550
	Weight	3790KGS	3900KGS	4450KGS	4550KGS	5200KGS	5400KGS	5500KGS	7850KGS
Genset Model		PC960	PC1000	PC1040	PC1125	PC1250	PC1380	PC1580	PC1900
Standby Power		963kVA	1000kVA	1038kVA	1125kVA	1250kVA	1375kVA	1575kVA	1875kVA
		770kW	800kW	830kW	900kW	1000kW	1100kW	1260kW	1500kW
Prime Power		875kVA	900kVA	938kVA	1000kVA	1125kVA	1250kVA	1375kVA	1575kVA
		700kW	720kW	750kW	800kW	900kW	1000kW	1100kW	1260kW
Ampere (base on 400V) A		1148.2	1181.0	1230.2	1312.2	1476.2	1640.2	1804.3	2066.7
Engine Brand		CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS	CUMMINS
Engine Model		KTA38-G1	KTA38-G2	KTA38-G2B	KTA38-G2A	KTA38-G4	KTA38-G9	KTA50-G3	KTA50-G9
Cylinder *Bore*Stroke		12×159×159mm	12×159×159mm	12×159×159mm	12×159×159mm	12×159×159mm	12×159×159mm	16×159×159mm	16×159×159mm
Displacement		37.8L	37.8L	37.8L	37.8L	37.8L	37.8L	50.3L	50.3L
Alternator Brand		SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA	SURIRELLA
Alternator Model		404B	404C	404C	404D	404E	404F	404G	454B
Alternator type		Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless	Brushless
Controller Model		6120	6120	6120	6120	6120	6120	6120	6120
Fuel consumption		194L/h	204L/h	204L/h	225L/h	245L/h	260L/h	291L/h	331L/h
Capacity(L)	Fuel tank	1300L	1400L	1400L	1400L	1400L	1400L	N/A	N/A
	Coolant	118L	118L	118L	118L	118L	118L	161L	165L
	Lubrication	114L	114L	114L	114L	114L	114L	151L	178L
Open type	Demension	4300*1800*2500	4300*1800*2500	4300*1800*2500	4300*1800*2500	4300*1800*2500	4300*1800*2500	5000*2150*2550	5200*2150*2550
	Weight	7200KGS	7300KGS	7300KGS	7350KGS	7400KGS	7600KGS	8900KGS	9960KGS
Sound proof	Dimension	5400*2200*2550	5400*2200*2550	5400*2200*2550	5400*2200*2550	5400*2200*2550	5400*2200*2550	6400*2200*2550	7200*2200*2550
	Weight	8400KGS	8500KGS	8500KGS	8550KGS	8600KGS	8800KGS	10600KGS	12100KGS